

How to Order

Use the **bold** characters from the chart below to construct a product code

SELECT:

- 4000** **L** **S** **B10** **00** **N** **0** **U1**
1. **4000** series
 2. Bridge Resistance: **L** is 1000 ohms
 3. Pressure Datum: **S** sealed gauge; **A** absolute
 4. Insert pressure range code from table below
 5. Pressure Port see chart
 6. Electrical Connection (mating connector sold separately)
 - N** Mil C-83723 size 10-5, screw lock connector; (Mating connector part # 499855-0001 and clamp # 499855-0011)
 - C** Mil C-26482 size 10-6, bayonet lock connector (Mating connector part # 166267-0006)

4000 Model Bar Ranges	Range Code	Absolute (A) Sealed (S)
0 to 1	A10	A
0 to 1.6	A16	A
0 to 2.5	A25	A
0 to 4	A40	A
0 to 6	A60	A
0 to 10	B10	S, A
0 to 16	B16	S, A
0 to 25	B25	S, A
0 to 40	B40	S, A
0 to 60	B60	S, A
0 to 100	C10	S, A
0 to 160	C16	S, A
0 to 250	C25	S, A
0 to 400	C40	S, A

Pressure Ports	Description
Code	
00	G 1/4 internal
A0	G 1/4 AT external
K0	7/16-20 UNF-3A external
M0	M14 x 1.5 external
P0	G1/2 AT external
B0	1/4-18 NPT external
G0	1/2-14 NPT external
S0	7/16-20 UNJF-3A, MS 33656E4

*For Pressure Port dimensions see page 39