



General data

LUMOTAST 75 IP65 pushbutton range

Illuminated pushbuttons and signal lamps with lamp socket T 4.5

- Mounting hole diameter 16.2 mm
- Degree of protection IP65
- Solder terminals for the following wire cross-sections:
 - Installed 0.5 mm² max.
 - Factory terminated 0.35 mm² max.
- 250 V/4 A max.
- 3 NC + 3 NO max.

LUMO
75 (65)

Content

LUMOTAST 75 illuminated pushbutton IP65

LUMOTAST 75 illuminated pushbutton IP65, flush lens, square collar	1 - 54
LUMOTAST 75 illuminated pushbutton IP65, protruding lens, square collar	1 - 56
LUMOTAST 75 illuminated pushbutton IP65, protruding lens, square collar	1 - 57
LUMOTAST 75 illuminated pushbutton IP65, flush lens, round collar	1 - 58
LUMOTAST 75 illuminated pushbutton IP65, protruding lens, round collar	1 - 59
LUMOTAST 75 illuminated pushbutton IP65, flush lens, rectangular collar	1 - 60

LUMOTAST 75 signal lamp IP65

LUMOTAST 75 signal lamp IP65, flush lens, square collar	1 - 62
LUMOTAST 75 signal lamp IP65, flush lens, square collar	1 - 63
LUMOTAST 75 signal lamp IP65, protruding lens, square collar	1 - 64
LUMOTAST 75 signal lamp IP65, flush lens, round collar	1 - 64
LUMOTAST 75 signal lamp IP65, protruding lens, round collar	1 - 65
LUMOTAST 75 signal lamp IP65, flush lens, rectangular collar	1 - 65