



Programmable counter ENTS90

Many programmable functions
Display shows preset value, counted value, contacts on/off
Front protection IP65 (waterproof)
Signal inputs for start/gate and reset
High efficient 13mm-LED-display, visible up to 5m
Internal power supply DC12V for connected sensors



Level control relay DSFC

Level control of liquid in tanks
Suitable for all liquids as water, marmalade, syrup...
Adjustable sensitivity up to 300kOhms and time delay
Size 22.5mm, DIN-rail mounting
Electrode without d.c. voltage



Electronic amplifier DSTC

Contacts switch in dependence of sensor resistance
Typical applications are thermo-relay, twilight-switch, contact protector..
Adjustable sensitivity up to 2MOhms
Optional interlocking contacts
Size 22.5mm, DIN-rail mounting



Thermistor motor protection relay DHC

High security by the reconnection-stop and principle of rest-current
Integrated acknowledgement key
Galvanic isolation of the sensor circuit
Easy installation of several PTC-sensor resistances at one unit
1 or 2 contacts
Size 22.5mm, DIN-rail mounting



Compact power supply with switching relay DNEZ5

Power supply DC24V for small components e.g. proximity switches or light barriers
Compact 45mm DIN-rail housing
Internal switching relay with 2 change-over contacts
DC24V/100mA stabilized and short-circuit-proof output voltage