

Position switch KL



Heavy-duty position switch
Numerous variants
Up to 1000 actuations/min
Temperature range: 125°C
Switching capacity: AC 250V, 16A
Screw terminals

Microswitch AS



Numerous variants
Temperature range: 85°C
Switching capacity: AC 250V, 16A
Screw terminals

Microswitch MS




Numerous variants
Temperature range: 85°C
Switching capacity: AC 250V, 5A
Solder terminals or plain connector terminals

Microswitch RSV



3mm-wide contact gap
Temperature range: 125°C
Switching capacity: AC 250V, 10A
Plain connector terminals

Microswitch US2




Application up to AC 500V
Temperature range: 125°C
Switching capacity: AC 250V, 6A
Overtravel button
Solder terminals

Microswitch SM


Small dimensions 20x10x6,4mm
Numerous variants
Temperature range: 80°C
Switching capacity: AC 250V, 5A
Solder terminals, soldering pins or plain connector terminals

Microswitch VMN



Numerous variants (actuator, terminals and actuation forces)
Temperature range: 80°C
Switching capacity: AC 250V, up to 15A
Solder terminals, soldering pins or plain connector terminals

Subminiature microswitch DM



Highly compact dimensions 13x7x6mm
Temperature range: 65°C
Switching capacity: AC 125V,3A
Soldering pin terminal